




CITY OF FAIRBANKS

• <

PROPOSED STORM DRAIN PROJECT


ITB-25-05

LATHROP DITCH IMPROVEMENTS



VICINTY MAP

			SCALE: _{N□NE}	DESIGNED: RHP/KLL	APPROVED
				DRAWN:	
				CHECKED: RHP	CITY ENGINEER
DATE	REVISION	BY		DATE: 01/24/2025	DATE



CITY OF FAIRBANKS, ALASKA Engineering Department

INDEX OF SHEETS

QUANTITIES AND GENERAL NOTES

STORM DRAIN PLAN & PROFILE

CITY OF FAIRBANKS STANDARD DETAILS — STORM DRAIN

TITLE SHEET

TYPICAL SECTION

SHEET NO.

A2 B1

U1 - U5

SD1 - SD2

DESCRIPTION

Project ITB-25-05

A1

OF 10
SHEETS

SUBSIDIARY QUANTITY ESTIMATES				
ITEM DESCRIPTION	UNIT	QUANTITY		
PIPE BEDDING	CUBIC YARD	1,505		
BACKFILL	CUBIC YARD	1,310		
SEEDING	SQUARE YARD	3,200		
HMA, TYPE II; CLASS B	TON	11		
ASPHALT BINDER, GRADE 52-28	TON	0.6		

GENERAL NOTES

- GRADES, ALIGNMENTS, APPROACH LOCATIONS, LENGTHS AND LOCATIONS OF CONDUIT RUNS SHOWN ON THESE PLANS ARE SUBJECT TO MINOR REVISIONS BY THE ENGINEER. ALL DISTANCES SHOWN IN THE PLANS ARE HORIZONTAL MEASUREMENTS
- SAWCUT ALL MATCH LINES WHERE NEW CONSTRUCTION OF PAVEMENT, SIDEWALK OR CURBING ABUTS EXISTING. SAWCUTS SUBSIDIARY TO RESPECTIVE PAY ITEMS.
- APPLY WATER FOR DUST CONTROL DAILY OR AS DIRECTED BY THE ENGINEER. PAY SUBSIDIARY TO PAY ITEM 643.0002.0000 TRAFFIC MAINTENANCE.
- 4. PAYMENT FOR PAY ITEM 202.0001.0000 REMOVAL OF STRUCTURES AND OBSTRUCTIONS SHALL BE A LUMP SUM PAYMENT FOR REMOVING ALL ITEMS IN CONFLICT WITH THE IMPROVEMENTS. THESE ITEMS ARE NOT LISTED. IT IS THE CONTRACTORS RESPONSIBILITY TO FIELD VERIFY THE NATURE OF THIS WORK BEFORE BIDDING.
- 5. ALL PAYMENTS REQUESTED BY THE CONTRACTOR SHALL BE DEVELOPED BY THE CONTRACTOR IN A FORM ACCEPTABLE TO THE ENGINEER. PAY ESTIMATES SHALL BE SUBMITTED BY THE CONTRACTOR AND APPROVED BY THE ENGINEER.
- 6. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THEIR OWN STAGING AREA.
- NUMEROUS UNDERGROUND UTILITIES EXIST WITHIN THE PROJECT CORRIDOR. THE CONTRACTOR SHALL CONTACT UTILITY OWNERS AND GET LOCATES PRIOR TO EXCAVATION.

ABBREVIATIONS

ABD - ABANDONED AC - ASPHALT CONCRETE AP - ANGLE POINT ABC - AGGREGATE

BASE COURSE BK SDWK - BACK OF SIDEWALK BLDG - BUILDING

BL - BASELINE

BOP - BEGINNING OF PROJECT BV - BUTTERFLY VALVE

C - CONDENSATE CB - CATCH BASIN CC - CURB CUT

CI - CAST IRON CL - CENTER LINE CONC - CONCRETE

CS - CONDENSATE SERVICE CSP - CORRUGATED STEEL PIPE

D - DUCT BANK

DIP - DUCTILE IRON PIPE

DL - DITCH LINE DG - DOWN GUY DW - DRIVEWAY

E - EAST

e - SUPERELEVATION

EA - EACH

ELEV - ELEVATION

EOP - END OF PROJECT EP - EDGE OF PAVEMENT

FS - FND SECTION

EXIST - EXISTING

FG - FINISH GRADE

FH - FIRE HYDRANT

FL - FLOW LINE FIG - FLANGE

FOC - FACE OF CURB

FRM - FRAMF

FW - FLUSHWELL

G - GUTTER

GP - GRADE POINT

GRP- GUARD POST GR - GRADE

GRT - GRATE GV - GATE VALVE

HB - HORIZONTAL BEND

HDPE - HIGH DENSITY POLYETHYLENE

HPS - HIGH PRESSURE SODIUM LUMINAIRE HWR - HOT WATER RETURN

HWS - HOT WATER SUPPLY

HWSS - HOT WATER SERVICE SUPPLY

ID - INSIDE DIAMETER

IE - INVERT ELEVATION INS - INSULATION

L - LENGTH OF CURVE

LTDL - LEFT DITCH LINE

LF - LINEAL FEET

MAX — MAXIMUM MB - MAILBOX

MH - MANHOLE

MIN - MINIMUM

MON - MONUMENT MV - MERCURY VAPOR LUMINAIRE NC - NORMALLY CLOSED NE - NORTHEAST NW - NORTHWEST

N - NORTH N.I.C. - NOT IN CONTRACT

OD - OUTSIDE DIAMETER OG - ORIGINAL GROUND

PC - POINT OF CURVATURE PCC - POINT OF COMPOUND CURVE

PI - POINT OF INTERSECTION

PIV - POST INDICATOR VALVE PL - PROPERTY LINE

POT - POINT ON TANGENT PRC - PROPERTY CORNER

PP - POWER POLE PT - POINT OF TANGENCY PLVC - POLYVINYL CHLORIDE

PUE - PERMANENT UTILITY EASEMENT PVC - POINT OF VERTICAL CURVATURE

PVI - POINT OF VERTICAL INTERSECTION PVMT - PAVEMENT

PVT - POINT OF VERTICAL TANGENCY

R - RADIUS

RTDL - RIGHT DITCH LINE RMC - RIGID METAL CONDUIT

ROW - RIGHT OF WAY

R&R - REMOVE AND REPLACE RT - RIGHT

RPM - REINFORCED PLASTIC MORTAR

SMTA - SELECTED MATERIAL TYPE A

s - SLOPE S - SOUTH

SE - SOUTHEAST SM - SEWER MAIN

SMH - SEWER MANHOLE SMHS- SEWER MANHOLES

SCH - SCHEDULE

SD - STORM DRAIN

SI - STREET INTERSECTION

 STREET LIGHT SP - STEEL PIPE

SS - SEWER SERVICE

ST - STEAM

STA - STATION

STS - STEAM SERVICE

SW - SOUTHWEST

T - TELEPHONE

TC -TOP OF CURB

TCP- TEMP. CONSTRUCTION PERMIT

TOC - TOP OF CONDUIT

TOP - TOP OF PIPE

TYP- TYPICAL

UG - UNDERGROUND

VB - VALVE BOX

W - WEST


WM - WATER MAIN

WS - WATER SERVICE

WSP - WOOD STAVE PIPE

02/19/2025

GENERAL NOTES, ABBREVIATIONS, AND ESTIMATE OF QUANTITIES






CITY OF FAIRBANKS, ALASKA **Engineering Department**


Project ITB-25-05

A2 OF 10 SHEETS




TYPICAL SECTION NOTE:

- 1. INSTALL NEW CPP PIPE IN EXISTING DITCH FLOWLINE OR AS DIRECTED BY THE ENGINEER.
- 2. NOTE, THE PIPE BEDDING DETAIL AS SHOWN ON THIS SHEET MODIFIES THE STANDARD PIPE BEDDING DETAIL SHOWN ON SHEET SD1.



PIPE BEDDING DETAIL

NOT TO SCALE



TYPICAL SECTION 02/19/2025

SCALE: DESIGNED: RHP/KLL APPROVED DRAWN: CHECKED: RHP CITY ENGINEER DATE: 01/24/2025 DATE BY



CITY OF FAIRBANKS, ALASKA **Engineering Department**

B1OF 10 SHEETS

LATHROP DITCH IMPROVEMENTS

Project ITB-25-05

- 1. CONTRACTOR TO VERIFY EXISTING DITCH ELEVATION AND EXISTING 48" CSP INVERT AND REPORT TO ENGINEER AS SHOWN ON SHEETS U1 AND U5 BEFORE INSTALLATION OF NEW 48-INCH CPP STORM DRAIN PIPE.
- 2. NO NEW STORM DRAIN PIPE TO BE INSTALLED ON THIS SHEET.

STORM DRAIN

CITY OF FAIRBANKS, ALASKA Engineering Department

Project ITB-25-05

OF 10 SHEETS

U1

SCALE: DESIGNED: RHP/KLL APPROVED 1"=40' HORIZ., 1"=4' VERT. DRAWN: "=20' HORIZ., 1"=2' VERT. (FULL SIZE) CITY ENGINEER CHECKED: RHP (HALF SIZE) DATE: 01/24/2025 DATE

1. NO NEW STORM DRAIN PIPE TO BE INSTALLED ON THIS SHEET.



1"=20' HORIZ., 1"=2' VERT. (FULL SIZE) REVISION

1"=40' HORIZ., 1"=4' VERT. (HALF SIZE)

DRAWN: CHECKED: RHP DATE: 01/24/2025


CITY ENGINEER DATE

LATHROP DITCH IMPROVEMENTS

CITY OF FAIRBANKS, ALASKA Engineering Department Project ITB-25-05

OF 10 SHEETS





- 1. INSTALL NEW 48" CPP STORM DRAIN PIPE IN EXISTING DITCH.
- 2. ENGINEER WILL PROVIDE TMBs AND STAKE ROW FOR OFFSET TO PIPE AND MANHOLES.
- 3. CONTRACTOR TO USE LOW PROFILE STORM DRAIN MANHOLE FRAMES (BASIS OF DESIGN: D&L PART # A-2107

STORM DRAIN

IONM DIVAIN	02/19/2025
CITY OF FAIRBANKS, AL Engineering Departmen	
Project ITB-25-0	5 OF 10 SHEETS

			SCALE:		DESIGNED: RHP/KLL	APPROVED
			1"=20' HORIZ.,	1"=40' HORIZ.,	DRAWN:	
			1"=2' VERT.	1"=4' VERT.	CHECKED: RHP	CITY ENGINEER
DATE	REVISION	BY	(FULL SIZE)	(HALF SIZE)	DATE: 01/24/2025	DATE





- 1. INSTALL NEW 48" CPP STORM DRAIN PIPE IN EXISTING DITCH.
- 2. ENGINEER WILL PROVIDE TMBs AND STAKE ROW FOR OFFSET TO PIPE AND MANHOLES.
- 3. CONTRACTOR TO USE LOW PROFILE STORM DRAIN MANHOLE FRAMES (BASIS OF DESIGN: D&L PART # A-2107

CITY	of	FAIRE	BANKS,	ALASKA
E	ngin	eering	Departi	ment

OF 10 Project ITB-25-05 SHEETS

SCALE: "=2' VERT. (FULL SIZE)

1"=4' VERT. (HALF SIZE)

1"=40' HORIZ.,

DESIGNED: RHP/KLL DRAWN: CHECKED: RHP DATE: 01/24/2025

APPROVED

DATE

CITY ENGINEER



U4

02/19/2025

- 1. CONTRACTOR TO VERIFY EXISTING DITCH ELEVATION AS SHOWN ON SHEET U1 AND EXISTING 48" CSP INVERT AS SHOWN ON SHEET U5 AND REPORT TO ENGINEER BEFORE INSTALLATION OF NEW 48-INCH CPP STORM DRAIN PIPE.
- 2. INSTALL NEW 48" CPP STORM DRAIN PIPE IN EXISTING DITCH.
- 3. ENGINEER WILL PROVIDE TMBs AND STAKE ROW FOR OFFSET TO PIPE AND MANHOLES.
- 4. CONTRACTOR TO USE LOW PROFILE STORM DRAIN MANHOLE FRAMES (BASIS OF DESIGN: D&L PART #A-2107).
- 5. CONTRACTOR TO PROVIDE STORMWATER BYPASS DURING STORM DRAIN INSTALLATION. ESTIMATED FLOW 561 GPM (MEASURED ON 2/14/2025) AND 552 GPM (MEASURED ON 2/18/2025). THIS WORK IS SUBSIDIARY TO PAY ITEM 603.0021.0048.

STORM DRAIN

CITY OF FAIRBANKS, ALASKA ${\bf Engineering\ Department}$ Project ITB-25-05

OF 10 SHEETS

U5


CITY ENGINEER




1"=40' HORIZ., 1"=4' VERT. (HALF SIZE)

DESIGNED: RHP/KLL DRAWN: CHECKED: RHP DATE: 01/24/2025 DATE


LATHROP DITCH IMPROVEMENTS





BEDDING DETAIL

NOT TO SCALE



MANHOLE R	EINFORCEMENT SC				
SECTION	MANHOLE	SIZE	(2)		
SECTION	48"	72"	(SHALL COMPLY WITH AASHTO M 199 /ASTM 478)		
FLAT BASE	0.39 SQ IN/FT EACH WAY	0.39 SQ IN/FT EACH WAY	*CIRCUMFERENTIAL		
RISER SECTION*	0.12 SQ IN/FT	0.18 SQ IN/FT	REINFORCING		
CONE SECTION*	0.12 SQ IN/FT	0.18 SQ IN/FT	ALL AREAS ARE MINIMUM CROSS—SECTIONAL AREA OF		
FLAT LID**	0.12 SQ IN/FT EACH WAY	0.12 SQ IN/FT EACH WAY	REINFORCEMENT PER FOOT OF SECTION.		
ADJUSTING RING	0.024 SQ IN	0.024 SQ IN			

**OPENINGS IN FLAT LIDS SHALL BE ADDITIONALLY REINFORCED WITH A MINIMUM OF THE EQUIVALENT OF 0.2 SQ IN OF STEEL AT 90°.



3/13/17	WATER STOP GASKETS	RHP
2/3/10	NEW SD1	GSC,RHP
3/23/07		RHP
DATE		RY


NOT TO SCALE


STAFF CHECKED: RHP,GSC DATE: 3/23/07


CITY OF FAIRBANKS, ALASKA **ENGINEERING DIVISION**

STANDARD DETAILS STORM DRAIN MANHOLES, THAW TUBES AND BEDDING SD1


TYPICAL CURB INLET







NO SUMP CATCH BASIN ALTERNATE USED WHERE INDICATED ON PLANS



EJIW T4DI

GRADE POINT

FRAME WITH ADJUSTABLE HOOD FOR

INSTALLATION IN CURB FACE

TOP OF GRATE

ELEVATION

BRICK OR BLOCK


SET IN GROUT, OR SET FRAME ON

CONCRETE BED

6"-11" RANGE OR APPROVED EQUAL 5 7 X 37 X 13". 3" RADIUS WEIGHT: 160 LBS EMBOSSED LETTERING: "DUMP NO WASTE! DRAINS TO RIVERS" WITH FISH IMAGE PERMANENTLY CAST INTO HOOD TOP.


EJIW 7030T4DI ADJUSTABLE HOOD WITH

EJIW 7030T3 BACK GRATE OR APPROVED EQUAL (WHEN INLET IS LOCATED IN CURB CUT DEPRESSED SECTION): GRATE: 7" X 37 \(\frac{3}{4} \)" W/ 12" R WEIGHT: 105 LBS.




FRAME WITH BACK GRATE FOR INSTALLATION IN CURB CUT

TYPICAL FIELD INLET EJIW 7700M1 GRATE (2) EA OR APPROVED EQUAL 17 3'" X 23 3/4" X 1 1/2' OPEN AREA: 128 SQ. IN. EJIW 7705Z HEAVY TRAFFIC LOADING FRAME WITH OPENINGS FOR (2) GRATES. WEIGHT: 216 LBS. —30 1/4" – EMBOSSED LETTERING: "DUMP NO POLLUTANTS"



INLET BOX/CATCH BASIN DETAILS

NOT TO SCALE



DEPRESSION IN FLOW LINE AT INLET

CATCH BASIN NOTES:

- 1. THE WORDS "INLET" AND "CATCH BASIN" SHALL BE INTERCHANGEABLE.
- 2. ALL GROUT SHALL BE NON-SHRINK. PROTECT GROUT DURING CURE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDED METHOD.
- 4. TYPICALLY, CATCH BASINS ARE NOT INSULATED. HOWEVER, SPECIAL CASES REQUIRE INSULATION OF ALL OUTSIDE SURFACES. SEE PLAN NOTE TO INSULATE CB.
- 5. GROUT THE INSIDE FACE OF ALL JOINTS SMOOTH.



2/3/10	NEW SD2	GSC,RHP
3/23/07		RHP
DATE	REVISION	BY

BASIN IS TO BE INSULATED

NOT TO SCALE

DESIGNED:	
DRAWN:	STAFF
CHECKED:	RHP,GSC
DATE:	3/23/07

CITY OF FAIRBANKS, ALASKA **ENGINEERING DIVISION**

STANDARD DETAILS STORM DRAIN CATCH BASIN