




CITY OF FAIRBANKS

PROPOSED ROADWAY PROJECT

PROJECT #: ITB-25-15

12TH & CUSHMAN IMPROVEMENTS



VICINTY MAP

SCALE: DATE REVISION BY

DESIGNED: APPROVED DRAWN: CHECKED: DATE: DATE

CITY ENGINEER

12TH & CUSHMAN **IMPROVEMENTS** 

CITY OF FAIRBANKS, ALASKA **Engineering Department** Project ITB-25-15

INDEX OF SHEETS

TITLE SHEET

SURVEY CONTROL

TYPICAL SECTION

TRAFFIC CONTROL PLAN

SHEET NO.

A2 А3

В1

F1 – F3

Q1

T1

CD1 - CD2

DESCRIPTION

ROADWAY PLAN & PROFILE, CROSS SECTIONS

GENERAL NOTES, ABBREVIATIONS, AND ESTIMATE OF QUANTITIES

EROSION & SEDIMENT CONTROL PLAN

CITY OF FAIRBANKS STANDARD DETAILS -

A1OF SHEETS

#### ABBREVIATIONS ABD - ABANDONED NC - NORMALLY CLOSED AC - ASPHALT CONCRETE NE - NORTHEAST AP - ANGLE POINT NW - NORTHWEST ABC - AGGREGATE N - NORTH N.I.C. - NOT IN CONTRACT BASE COURSE BK SDWK - BACK OF SIDEWALK OD - OUTSIDE DIAMETER BLDG - BUILDING OG - ORIGINAL GROUND BL - BASELINE BOP - BEGINNING OF PROJECT PC - POINT OF CURVATURE BV - BUTTERFLY VALVE PCC - POINT OF COMPOUND CURVE PI - POINT OF INTERSECTION C - CONDENSATE CB - CATCH BASIN PIV - POST INDICATOR VALVE CC - CURB CUT PL - PROPERTY LINE CI - CAST IRON POT - POINT ON TANGENT CL - CENTER LINE PRC - PROPERTY CORNER CONC - CONCRETE PP - POWER POLE CS - CONDENSATE SERVICE PT - POINT OF TANGENCY CSP - CORRUGATED STEEL PIPE PLVC - POLYVINYL CHLORIDE PUE - PERMANENT UTILITY EASEMENT D - DUCT BANK PVC - POINT OF VERTICAL CURVATURE DIP - DUCTILE IRON PIPE PVI - POINT OF VERTICAL INTERSECTION DL - DITCH LINE PVMT - PAVEMENT DG - DOWN GUY PVT - POINT OF VERTICAL TANGENCY DW - DRIVEWAY R - RADIUS E - EAST RTDL - RIGHT DITCH LINE e - SUPERELEVATION RMC - RIGID METAL CONDUIT EA - EACH ROW - RIGHT OF WAY ELEV - ELEVATION R&R - REMOVE AND REPLACE EOP - END OF PROJECT RT - RIGHT EP - EDGE OF PAVEMENT RPM - REINFORCED PLASTIC MORTAR ES - END SECTION EXIST - EXISTING SMTA - SELECTED MATERIAL TYPE A s - SLOPE FG - FINISH GRADE S - SOUTH FH - FIRE HYDRANT SE - SOUTHEAST SM - SEWER MAIN FL - FLOW LINE FIG - FLANGE SMH - SEWER MANHOLE FOC - FACE OF CURB SMHS- SEWER MANHOLES FRM - FRAME SCH - SCHEDULE FW - FLUSHWELL SD - STORM DRAIN SI - STREET INTERSECTION G - GUTTER SL - STREET LIGHT GP - GRADE POINT SP - STEEL PIPE GRP- GUARD POST SS - SEWER SERVICE GR - GRADE ST - STEAM GRT - GRATE STA - STATION GV - GATE VALVE STS - STEAM SERVICE SW - SOUTHWEST HB - HORIZONTAL BEND HDPE - HIGH DENSITY POLYETHYLENE T - TELEPHONE HPS - HIGH PRESSURE SODIUM LUMINAIRE TC -TOP OF CURB HWR - HOT WATER RETURN TCP- TEMP. CONSTRUCTION PERMIT HWS - HOT WATER SUPPLY TOC - TOP OF CONDUIT HWSS - HOT WATER SERVICE SUPPLY TOP - TOP OF PIPE TYP- TYPICAL ID - INSIDE DIAMETER IE - INVERT ELEVATION UG - UNDERGROUND INS - INSULATION VB - VALVE BOX L - LENGTH OF CURVE

LTDL - LEFT DITCH LINE

MV - MERCURY VAPOR LUMINAIRE

LT - LEFT

LF - LINEAL FEET

MAX - MAXIMUM MB - MAILBOX MH - MANHOLE MIN - MINIMUM MON - MONUMENT

### GENERAL NOTES

- 1. GRADES, ALIGNMENTS, APPROACH LOCATIONS, LENGTHS AND LOCATIONS OF CONDUIT RUNS SHOWN ON THESE PLANS ARE SUBJECT TO MINOR REVISIONS BY THE ENGINEER. ALL DISTANCES SHOWN IN THE PLANS ARE HORIZONTAL MEASUREMENTS.
- 2. SAWCUT ALL MATCH LINES WHERE NEW CONSTRUCTION OF PAVEMENT, SIDEWALK OR CURBING ABUTS EXISTING. SAWCUTS SUBSIDIARY TO RESPECTIVE PAY ITEMS.
- 3. APPLY WATER FOR DUST CONTROL DAILY OR AS DIRECTED BY THE ENGINEER. PAY SUBSIDIARY TO PAY ITEM 643.0002.0000 TRAFFIC MAINTENANCE.
- 4. PAYMENT FOR PAY ITEM 202.0001.0000 REMOVAL OF STRUCTURES AND OBSTRUCTIONS SHALL BE A LUMP SUM PAYMENT FOR REMOVING ALL ITEMS IN CONFLICT WITH THE IMPROVEMENTS. THESE ITEMS ARE NOT LISTED, IT IS THE CONTRACTORS RESPONSIBILITY TO FIELD VERIFY THE NATURE OF THIS WORK BEFORE BIDDING.
- 5. ALL PAYMENTS REQUESTED BY THE CONTRACTOR SHALL BE DEVELOPED BY THE CONTRACTOR IN A FORM ACCEPTABLE TO THE ENGINEER. PAY ESTIMATES SHALL BE SUBMITTED BY THE CONTRACTOR AND APPROVED BY THE ENGINEER.
- 6. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THEIR OWN STAGING AREA.
- 7. NUMEROUS UNDERGROUND UTILITIES EXIST WITHIN THE PROJECT CORRIDOR. THE CONTRACTOR SHALL CONTACT UTILITY OWNERS AND GET LOCATES PRIOR TO EXCAVATION.
- 8. PRESERVE AND PROTECT EXISTING LANDSCAPE AND FENCING IN PLACE. SUBSIDIARY TO PAY ITEM 202.0001.0000.
- 9. ALL EXISTING ASPHALT PAVEMENT REMOVED SHALL BE DELIVERED TO THE CITY OF FAIRBANKS PUBLIC WORKS YARD AT 2121 PEGER ROAD. PAY SUBSIDIARY TO ITEM 202.0001.0000 REMOVAL OF STRUCTURES AND OBSTRUCTIONS.

PAY ITEM	DESCRIPTION	UNIT	UNIT PRICE	QTY
202.0001.0000	REMOVAL OF STRUCTURES AND OBSTRUCTIONS	LUMP SUM	\$	ALL REQUIRED
203.0003.0000	UNCLASSIFIED EXCAVATION	CY	\$	180
301.0001.00D1	AGGREGATE BASE COURSE GRADING D-1	TON	\$	80
304.0001.000F	SUBBASE, GRADING F	TON	\$	150
401.0001.002B	HMA, TYPE II; CLASS B	TON	\$	85
401.0004.0000	ASPHALT BINDER, GRADE 52-28	TON	\$	5
609.0010.0001	CURB TYPE, CATCH	LF	\$	57
609.0011.0001	CURB TYPE, VALLEY GUTTER	LF	\$	90
626.2014.0000	ADJUST FLUSHWELL	EACH	\$	2
627.0003.0000	INSTALL VALVE BOX	EACH	\$	1
640.0001.0000	MOBILIZATION AND DEMOBILIZATION	LUMP SUM	\$	ALL REQUIRED
641.2000.0000	POLLUTION CONTROL	LUMP SUM	\$	ALL REQUIRED
642.0001.0000	CONSTRUCTION SURVEYING	LUMP SUM	\$	ALL REQUIRED
643.0002.0000	TRAFFIC MAINTENANCE	LUMP SUM	\$	ALL REQUIRED
643.0023.0000	TRAFFIC PRICE ADJUSMENT	CONTIGENT SUM	\$	ALL REQUIRED

TABLE OF ESTIMATING FACTORS				
ITEM NO.	PAY ITEM	ESTIMATING FACTOR	UNIT	
301.0001.00D1	AGGREGATE BASE COURSE, GRADING D-1	145	LBS/CF	
304.0001.000F	SUBBASE, GRADING F	2	TON/CY	
401.0001.002B	HMA, TYPE II; CLASS B	150	LBS/CF	
401.0004.5228	ASPHALT BINDER, GRADE 52-28	5.5	% OF HMA PAY ITEM	

ABBREVIATIONS, GENERAL NOTES AND ESTIMATE OF QUANTITIES



			SCALE:	DESIGNED:	APPROVED	
					4	
				DRAWN:		
				2.0.000		
				CHECKED:	CITY ENGINEER	
DATE	REVISION	BY		DATE:	DATE	
5,	1121101011					

W - WEST


WM - WATER MAIN


WS - WATER SERVICE WSP - WOOD STAVE PIPE





12TH & CUSHMAN IMPROVEMENTS

CITY OF FAIRBANKS, ALASKA Engineering Department Project ITB-25-15 A2
OF
SHEETS









DATE:


DATE

REVISION

BY

DATE

OF SHEETS



SCALE:

BY

DATE

1"=20' HORIZ., 1"=40' HORIZ., 1"=4' VERT. 1"=8' VERT. (FULL SIZE) (HALF SIZE)

DESIGNED:

DRAWN:

DATE:

CHECKED:

APPROVED

DATE

CITY ENGINEER

CROSS SECTIONS

12TH & CUSHMAN

**IMPROVEMENTS** 

CITY OF FAIRBANKS, ALASKA Engineering Department

F3 OF Project ITB-25-15 SHEETS

### PROJECT SITE INFORMATION

- 1. SITE FUNCTION: STORM DRAIN INSTALLATION
- 2. MEAN ANNUAL PRECIPITATION: 10.53 INCHES AT FAIRBANKS INTERNATIONAL AIRPORT SOURCE: https://wrcc.dri.edu/cgi-bin/cliMAIN.pl?ak2968
- 3. 2-YEAR, 24-HOUR RAINFALL EVENT: 1.09 INCHES, STATION: FAIRBANKS F.O. SITE ID: 10-0215 (SOURCE: SOURCE: https://hdsc.nws.noaa.gov/pfds/pfds\_map\_ak.html
- PROJECT AREAS ARE LISTED BELOW, MATERIAL SITES NOT INCLUDED: PROJECT AREA: 0.15 ACRES DISTURBED AREA: 0.15 ACRES PRE-CONSTRUCTION PERCENT IMPERVIOUS AREA: 66 POST CONSTRUCTION PERCENT IMPERVIOUS AREA: 66 PRE-CONSTRUCTION RUNOFF COEFFICIENT: 0.60 POST-CONSTRUCTION RUNOFF COEFFICIENT: 0.60
- 5. MATERIAL SITES: MATERIALS WILL BE CONTRACTOR FURNISHED.
- LANDSCAPE TOPOGRAPHY: VERY FLAT RESIDENTIAL DEVELOPMENT IN PROJECT CORRIDOR. EXISTING SLOPES IN THIS AREA ARE RELATIVELY FLAT WITH POSITIVE DRAINAGE AWAY FROM STRUCTURES AND ROADS INTO EXISTING STORM DRAIN INFRASTRUCTURE.
- DRAINAGE PATTERNS: SURFACE DRAINAGE VIA PIPED STORM DRAIN SYSTEM FLOWS TO THE CHENA RIVER VIA EXISTING WICKERSHAM STREET OUTFALL.
- 8. STAGING AND STOCKPILE AREAS: CONTRACTOR MUST SEEK LOCATIONS FOR STOCKPILING MATERIAL AND STAGING AND STORAGE OF EQUIPMENT.

# ENVIRONMENTAL INFORMATION

- 1. RECEIVING WATERS: CHENA RIVER, FAIRBANKS MS4
- 2. IMPAIRED WATER BODIES: NONE
- 3. TOTAL MAXIMUM DAILY LOAD (TDML): NONE
- STORM SEWER / DRAINAGE SYSTEMS: CITY OF FAIRBANKS MS4 CONSISTING OF PIPED AND SURFACE WATER DRAINAGE NETWORK TO OUTFALLS AT CHENA RIVER.
- THREATENED AND ENDANGERED SPECIES: NONE
- 6. HISTORICAL & CULTURAL RESOURCE PRESENCE: NONE
- FISH & WILDLIFE HABITAT PRESENCE: ALL CONSTRUCTION ACTIVITIES SHALL COMPLY WITH THE MIGRATORY BIRD TREAT ACT TO PREVENT THE KILLING OR TAKING OF MIGRATORY BIRDS OR ANY PART, NEST, OR EGG OF ANY SUCH BIRDS.
- 8. EXISTING PUBLIC WATER SYSTEM (PWS) DRINKING WATER PROTECTION AREAS:
  - PWSID: AK2310730
  - WATER SYSTEM NAME: GOLDEN HEART UTILITIES
  - PWS CONTACT INFORMATION NAME: TARIK SPEAR

PHONE: (907) 455-4444 EMAIL: TÀRIK.SPEAR@AKWATER.COM

ADDRESS: 3691 CAMERON ST #201, FAIRBANKS, AK 99709

GRATE? HANDLING CURB INSERT DEFLECTOR FOR OPEN-FILTER BAG CURB STYLE INLETS CATCH BASIN OUTLET

CATCH BASIN INLET PROTECTION DETAIL

LEGEND

STORM DRAIN MANHOLE


STORM DRAIN INLET

STORM DRAIN PIPE

PIPE FLOW DIRECTION

CATCH BASIN & CULVERT PROTECTION AREA

CATCH BASINS THAT REQUIRE INLET PROTECTION



## EROSION & SEDIMENT CONTROL PLAN

1. THIS PROJECT IS UNDER ONE ACRE AND WILL NOT BE REQUIRED TO DEVELOP A SWPPP OR FILE AN NOI WITH ADEC. EVEN IF THIS PROJECT DOES NOT NEED PERMIT COVERAGE, EROSION AND SEDIMENT CONTROLS WILL BE REQUIRED AND WATER QUALITY WILL BE PROTECTED.

- 2. THIS SHEET CONTAINS A PLAN VIEW OF 12TH AVE AT CUSHMAN STREET AND ITS EXISTING STORM DRAIN SYSTEM, INCLUDING ALL KNOWN STORM DRAIN INLETS, MANHOLES, AND PIPED SECTIONS. THE CONTRACTOR SHALL SELECT AND APPLY APPROPRIATE CONTROLS TO PREVENT SEDIMENT AND OTHER POLLUTANTS FROM ENTERING THE PIPED STORM DRAIN SYSTEM AND DISCHARGING TO THE CHENA RIVER.
- 3. HAVE A SPILL KIT AVAILABLE AT EACH WORK AREA WHEN HEAVY EQUIPMENT IS BEING UTILIZED.
- 4. ALL ENTRANCE AND EXITS WILL BE SWEPT AT A FREQUENCY TO MINIMIZE THE TRACK OUT FORM THE PROJECT OR AS DIRECTED BY THE ENGINEER.

TEMPORARY BEST MANAGEMENT PRACTICES (BMPS)

- 1. BEST MANAGEMENT PRACTICES (BMPS) IMPLEMENTED ON THIS PROJECT WILL UTILIZE THE SPECIFICATIONS PROVIDED IN THE ALASKA DEPARTMENT OF ENVIRONMENTAL CONSERVATION STORM WATER GUIDE OR THE DOT&PF BMP GUIDE, WHENEVER POSSIBLE.
- 2. INSTALL EROSION AND SEDIMENT CONTROL BMP'S PRIOR TO THE START OF CONSTRUCTION, AS NECESSARY TO MINIMIZE EROSION FROM DISTURBED SURFACES AND CAPTURE SEDIMENT ONSITE.
- 3. AT A MINIMUM, INLET PROTECTION (I.E. FILTER BAGS PLACED UNDER THE INLET GRATE) SHALL BE PROVIDED AT ALL INLETS WITHIN AND IMMEDIATELY ADJACENT TO THE PROJECT LIMITS.
- 4. MAINTAIN BMPS ON A REGULAR BASIS INCLUDING. BUT NOT LIMITED TO, REMOVAL AND DISPOSAL OF SEDIMENT AND REPLACING DAMAGED BMPS OR AS DIRECTED BY THE ENGINEER.

HAZARDOUS MATERIAL CONTROL PLAN (HMCP)

- 1. SUBMIT AN ELECTRONIC COPY TO THE ENGINEER FOR APPROVAL. THE CITY WILL REVIEW THE HMCP SUBMITTAL WITHIN 14 DAYS AFTER IT IS RECEIVED.
- 2. PREPARE THE HMCP FOR PREVENTION OF POLLUTION FROM STORAGE, USE, CONTAINMENT, CLEANUP, AND DISPOSAL OF ALL HAZARDOUS MATERIALS, INCLUDING PETROLEUM PRODUCTS RELATED TO CONSTRUCTION ACTIVITIES AND EQUIPMENT. COMPILE MATERIAL SAFETY DATA SHEETS IN ONE LOCATION AND REFERENCE THAT LOCATION IN THE HMCP
- 3. DESIGNATE A CONTRACTOR'S SPILL RESPONSE FIELD REPRESENTATIVE WITH 24 HOUR CONTACT INFORMATION. DESIGNATE A SUBCONTRACTOR SPILL RESPONSE COORDINATOR FOR EACH SUBCONTRACTOR. THE SUPERINTENDENT AND CONTRACTOR'S SPILL RESPONSE FIELD REPRESENTATIVE MUST HAVE 24 HOUR CONTACT INFORMATION FOR EACH SUBCONTRACTOR SPILL RESPONSE COORDINATOR AND THE UTILITY SPILL RESPONSE COORDINATOR.

1. ENSURE LOADS ARE STABLE OR COVERED SO THAT NO MATERIAL ESCAPEMENT OCCURS DURING HAULING ACTIVITIES.

SCALE: NONE DATE REVISION BY

**DESIGNED: STAFFI** APPROVED DRAWN: WKR CITY ENGINEER CHECKED: TZ DATF. DATE



12TH & CUSHMAN **IMPROVEMENTS** 

CITY OF FAIRBANKS, ALASKA Engineering Department

Project ITB-25-15

OF SHEETS

### CONSTRUCTION REQUIREMENT NOTES



MAINTAIN PEDESTRIAN ACCESS TO DOORWAYS OF INSURANCE BUILDING.

#### TRAFFIC CONTROL GENERAL NOTES

- 1. THESE TRAFFIC CONTROL PLANS (TCPs) ARE GENERAL IN NATURE. CONTRACTOR TO PROVIDE DETAILED TRAFFIC CONTROL PLANS TO ENGINEER FOR APPROVAL. NO WORK SHALL BEGIN WITHOUT AN APPROVED TCP.
- 2. REFER TO THE ALASKA TRAFFIC MANUAL (ATM) CURRENT EDITION FOR TRAFFIC CONTROL PLAN SPECIFICATIONS.
- 3. IMPLEMENT ONLY ONE TRAFFIC CONTROL SETUP AT A TIME AND RESTORE FULL FUNCTION AS SOON AS PRACTICABLE.
- 4. ALL SIGNS AND BARRICADES SHALL MEET REQUIREMENTS OF THE CURRENT ALASKA TRAFFIC MANUAL (ATM), MUTCD, AND ALASKA SIGN DESIGN SPECIFICATION (ASDS). THE FINAL JUDGMENT IN THE SELECTION, NUMBER AND APPLICATION OF THE TRAFFIC CONTROL DEVICES AND LOCATION OF ALL TRAFFIC CONTROL MEASURES WILL REST WITH THE ENGINEER.
- 5. EXISTING SIGNS WHICH CONFLICT WITH CONSTRUCTION SIGNING SHALL BE COVERED DURING PROJECT.
- CONSTRUCTION SIGNING SPECIFIED MAY BE ALTERED BY THE ENGINEER TO MEET CHANGING CONDITIONS AND TO PROTECT THE TRAVELING PUBLIC.
- 7. BARRICADE SETUPS SHALL HAVE 1 OPERABLE FLASHING LIGHT FOR EACH 10 FEET OF BARRICADE, WITH A MINIMUM OF 2 LIGHTS PER TYPE III BARRICADE. EXCEPT IN A TAPER WHERE ONLY THE FIRST TWO LIGHTS SHALL FLASH (TYPE A) AND THE REMAINDER SHALL BE STEADY BURN (TYPE C).
- 8. WHEN STREETS ARE RESTRICTED TO ONE LANE, THE MINIMUM CLEAR WIDTH SHALL BE 12' UNLESS OTHERWISE SPECIFIED ON AN APPROVED TRAFFIC CONTROL PLAN (TCP) OR AS DIRECTED BY THE ENGINEER.
- 9. ACCESS SHALL BE MAINTAINED FOR THE PASSAGE OF EMERGENCY VEHICLES THROUGH THE PROJECT.
- 10. ACCESS SHALL BE PROVIDED TO RESIDENTIAL PROPERTIES CONTINUOUSLY. CLOSURES SHALL NOT OCCUR WITHOUT PRIOR WRITTEN APPROVAL OF THE ENGINEER. COORDINATE CLOSURE PLANS WITH THE AFFECTED PROPERTY OWNERS. NOTIFY OWNERS A MINIMUM OF 48 HOURS PRIOR TO IMPLEMENTATION OF AN APPROVED CLOSURE.
- 11. PEDESTRIAN FLAGGERS SHALL BE PROVIDED FOR PUBLIC ACCESS AS REQUIRED THROUGHOUT THE PROJECT LIMITS.
- 12. ALTERNATE ACCESS MAY ALSO BE USED AS PART OF AN APPROVED TRAFFIC CONTROL PLAN. ALTERNATE ACCESS ROUTES SHALL BE CLEARLY SIGNED.
- 13. TYPE "A" FLASHING WARNING LIGHTS SHALL BE USED TO MARK THE TYPE III BARRICADES, ROAD CLOSURES AND ADVANCE DETOUR SIGNING AT NIGHT.
- 14. CONTRACTOR SHALL INTEGRATE TRAFFIC CONTROL WITH OTHER CONSTRUCTION IN THE AREA AS APPLICABLE.
- 15. CONTRACTOR SHALL PROVIDE AFFECTED PROPERTY OWNERS NOTICE OF CONSTRUCTION A MAXIMUM OF 3 WEEKS AND A MINIMUM OF 1 WEEK PRIOR TO CONSTRUCTION. NOTICE TO INCLUDE NEWSPAPER ADVERTISEMENT AND FLYERS TO BUSINESS
- 16. ALL SPECIAL SIGNS SHALL BE FABRICATED OF MATERIALS CONFORMING TO SECTION 615 OF THE SPECIFICATIONS.
- 17. TEMPORARY DRIVING SURFACE SHALL AT A MINIMUM BE COMPACTED GRAVEL OR AS APPROVED BY THE ENGINEER.

TRAFFIC CONTROL PLAN

1"=50' HORIZ. 1"=100' HORIZ. (FULL SIZE) (FULL SIZE)

DESIGNED: WKR DRAWN: WKR CHECKED: TZ DATE:

**APPROVED** 

DATE


CITY ENGINEER


12TH & CUSHMAN **IMPROVEMENTS** 


CITY OF FAIRBANKS, ALASKA Engineering Department

T1 OF SHEETS

Project ITB-25-15








### FLAT SURVEY MARKER DETAIL A

NOT TO SCALE





07/01/25

4/19/22	UPDATED MON. CASE, DEL. STEEL, ADDED PVC/HDPE	
11/19/14	JUNCTION BOX ADDED	RHP,STC
2/1/10	NEW CD2	RHP,GSC
10/27/08		RHP
DATE	REVISION	BY

DESIGNED:

DRAWN: STAFF

CHECKED: RHP,GSC

DATE: 3/23/07

CITY OF FAIRBANKS, ALASKA ENGINEERING DIVISION